

# EAVES FILLER DATA SHEET

## CLOSED CELL CROSS LINKED POLYETHYLENE FOAM

### Typical Physical Properties

Colour:	Black or White
Material	Low density, cross linked polyethylene
Length	800-1000mm depending on profile
Density	30kg/m <sup>3</sup>
Water Absorption	0.002g/cm <sup>3</sup>
Tensile Strength	270kPa
Elongation	125%
Tear Strength	16N/cm
Compressive Set	10%

### Applications Guide

Foam Sealant Pty Ltd recommends pre-testing all products under individual application conditions and materials used prior to commercial use.

### Typical Applications

Corrugated and water storage roofing

**Disclaimer** All figures shown above represent typical test results in laboratory conditions, and are given without guarantee since the conditions of use are beyond the control of our company. Width and thickness tolerances +/- 20%. It is the customer's responsibility to satisfy themselves that the product is fit for the purpose for which they intend to use it and that the actual conditions of use are suitable.

### FOAM Sealant Pty Ltd

ACN 068 983 755 ABN 83 197 550 989

48-52 Micro Circuit Dandenong South 3175 Victoria

Telephone (03) 9702 9989 Facsimile (03) 9799 6304

Email [sales@foamsealant.com.au](mailto:sales@foamsealant.com.au)



**Black or White  
Closed Cell Cross  
Linked Low  
Density  
Polyethylene Foam  
Protection Strips.**

**Provide excellent  
weather, chemical and  
pest resistance**

**Maintain roof insulation  
and provide protection**

**Interlocking dovetail  
joints eliminate gaps  
and provide for easy  
installation**

**Semi-rigid for easier  
handling and fixing**

**Available in all industry  
profiles**

### Limited Warranty

For a period of six months from the date of first sale, FOAM Sealant Pty Ltd warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving to be defective, or at our option, to refund the purchase price thereof.

The user assumes all other risk if any, including the risk of injury, loss or damage, direct or consequential arising out the use, misuse or inability to use this product. This warranty is in lieu of the warranties of merchantability, fitness for particular purpose and all other warranties expressed or implied. No deviation is authorised.