

FS120 DATA SHEET



FS120
Is an open cell
polyurethane
foam with an
aggressive
acrylic adhesive

- Maintains a light and dust seal at a minimum 50% compression.
- Remains flexible at a wide range of operation temperatures.
- Dimensionally stable. Will not ooze, run or drip.
- Easily removable liner minimises stretching during installation.
- Good temperature resistance.

Typical Physical Properties

Colour:	Grey
Thickness / Hardness:	3, 6, 9, 12 & 18mm / Soft
Density:	28kg/cm ³
Elongation	5
90° Peel Adhesion:	405

Parameter values are not guaranteed and will differ from lot to lot.

Application Guide

Surfaces should be clean before applying. Avoid touching adhesive surface before application. Press firmly to ensure good adhesion.

Typical Applications

Automotive gaskets and seals, refrigeration, air conditioning, cushioning applications, draught excluder.

NB: Product is not recommended for water seals.

Disclaimer All figures shown above represent typical test results in laboratory conditions, and are given without guarantee since the conditions of use are beyond the control of our company. Width and thickness tolerances +/- 20%. It is the customer's responsibility to satisfy themselves that the product is fit for the purpose for which they intend to use it and that the actual conditions of use are suitable.

Limited Warranty

For a period of six months from the date of first sale, FOAM Sealant Pty Ltd warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving to be defective, or at our option, to refund the purchase price thereof.

The user assumes all other risk if any, including the risk of injury, loss or damage, direct or consequential arising out the use, misuse or inability to use this product. This warranty is in lieu of the warranties of merchantability, fitness for particular purpose and all other warranties expressed or implied. No deviation is authorised.

FOAM Sealant Pty Ltd

ACN 068 983 755 ABN 83 197 550 989

48-52 Micro Circuit Dandenong South 3175 Victoria
Telephone (03) 9702 9989 Facsimile (03) 9799 6304
Email sales@foamsealant.com.au