

Material Safety Data Sheet

MSDS No. 1075

Revised: 05/24/2006

Section 1 - Chemical Product and Company Identification

Product Name: Normount Acrylic Tape, A3100, A3200 and A3300
Chemical Name: Acrylic Tape
Manufacturer: Saint-Gobain Performance Plastics, 1 Sealants Park, Granville, NY 12832
Phone (518) 642-2200, Fax (518) 642-1792
Emergency Telephone Number: ChemTel (800) 255-3924

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Section 2 - Composition / Information on Ingredients

Exempt from regulation because tape is an "article" that does not release or otherwise result in exposure to a hazardous chemical under normal use.

Section 3 - Physical and Chemical Properties

Physical State: Solid Foam Coated with Acrylic Adhesive
Water Solubility: Insoluble

Section 4 - Fire-Fighting Measures

Flash Point/Method: Not Applicable
Fire Extinguishing Media: Water, CO₂, or dry chemicals
Unusual Fire or Explosion Hazards: Not Applicable
Hazardous Combustion Products: CO
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Section 5 - Stability and Reactivity

Stability: Stable
Conditions to Avoid: None
Hazardous Decomposition Products: Could produce CO and CO₂

Section 6 - Health Hazard Information

Potential Health Effects

Emergency and First Aid Procedures: Not Applicable
Effects of Overexposure: Not Applicable
Carcinogenicity: IARC, NTP, and OSHA do not list as a carcinogen.

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Not Applicable
Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).
Disposal: Follow applicable Federal, state, and local regulations.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: None
Protective Clothing/Equipment: None
Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling Precautions: None
Storage Requirements: Store under 110°F for best performance

Disclaimer: The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, Saint-Gobain Performance Plastics Corporation makes no warranty with respect to the accuracy of the information or suitability of the recommendations, and assumes no liability to any use thereof.