

A7300 SERIES

Gray, Double-Sided, Acrylic Foam Tape



FOAM Sealant

ISO 9001:2015 CERTIFIED

Norbond® A7300 series is a grey, double-sided, coated acrylic foam tape with outstanding viscoelastic and adhesion properties. It offers ideal bonding performance for many interior and exterior industrial applications. Formulated for durable, long-lasting adhesion, A7300 exceeds industry standards for shear strength and bonding to high surface energy substrates, even at elevated temperatures.

The A7300 series viscoelastic core is specially designed to provide the following features:


- Great conformability and stretching
- Resistance to weathering degradation (UV and high temperature)
- Excellent performance in T-block and dynamic shear
- Outstanding static shear adhesion
- Durable adhesion at elevated temperature
- Shock and stress absorption

Available Sizes

Standard thickness: 0.5mm (.020 in.), 0.8mm (.031 in.), 1.1mm (.043 in.)

Master roll size: 800mm (31.5 in.) × 33m (108 ft)

Special thickness and roll sizes also available.



Applications

- Signage/display bonding
- Bus, truck and trailer skin bonding
- Bus, truck and trailer roof bow bonding
- Replacement of permanent fastening systems (rivets, welds and liquid adhesives) used in general industrial applications



FOAM Sealant Pty Ltd

SYDNEY | MELBOURNE | BRISBANE | PERTH

E sales@foamsealant.com.au | P 1300 000 205 | W foamsealant.com.au

ACN 068 983 755 ABN 83 197 550 989 Copyright © Foam Sealant 2021



Norbond A7300 – Properties

Performance tests are run using standard test procedures. The values presented are typical values and should not be used for specification purposes.



Thickness	90° Peel Adhesion ¹ (3-day dwell)				T-Block ²	Dynamic Shear ³	Static Shear ⁴	Service Temperature
	Without Liner	Glass	Aluminium	Stainless Steel	PMMA	Aluminium	Stainless Steel	
mm (in.)	N/cm (lb/in)	N/cm (lb/in)	N/cm (lb/in)	N/cm (lb/in)	N/cm ² (lb/in ²)	N/cm ² (lb/in ²)	7 days/1 kg	
0.5 (.020)	21 (12)	30 (17)	19 (11)	16 (9)	59 (86)	46 (67)	Pass and Exceeds	-35°C to 93°C (-30°F to 200°F)
0.8 (.031)	28 (16)	39 (22)	24 (14)	22 (13)	76 (110)	43 (62)	Pass and Exceeds	-35°C to 93°C (-30°F to 200°F)
1.1 (.043)	35 (20)	57 (33)	34 (20)	29 (17)	69 (100)	33 (48)	Pass and Exceeds	-35°C to 93°C (-30°F to 200°F)

¹ Based on ASTM D3330

³ Based on ASTM D1002

² Based on ASTM D897

⁴ Based on ASTM D3654

Options (subject to minimum order requirements)

Liner: A variety of substrate options (thickness, polymer, colour, graphic printed) and release level options are available upon request.

Important Instructions

- Because Sain Gobain cannot anticipate or control every potential application, we strongly recommend testing of this product under individual application conditions prior to commercial use.
- Surfaces must be clean and free of oil, grease, moisture, dust and dirt. Isopropyl alcohol is good for cleaning the surface.
- Apply a uniform pressure of 103 kPa (15 psi) to promote good contact between the material to be bonded and the tape. The application temperature should be between 16°C to 52°C (60°F and 125°F). It is not recommended to apply these tapes at temperatures below 16°C (60°F), as the adhesive does not flow in this condition and can result in poor bonding.
- The adhesion between the substrate and the tape increases with time, typically reaching final bond strength in 72 hours. Heating the product above 40°C (105°F) will accelerate the adhesion process.

Shelf Life

24 months after the date of manufacture when stored in original packaging at temperatures up to 21°C (70°F) and 50% relative humidity.



IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 24 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

For more information see: www.tapesolutions.saint-gobain.com