



FOAM Sealant

ISO 9001:2015 CERTIFIED

DATA SHEET

FS420 | 460

FS520 | 560

FS420, FS460, FS520, FS560 PE Sealant

FS420, FS460, FS520, FS560 PE Sealant for general vibration, sealing and closure applications

- Maintains a water tight seal at a minimum of 10% compression
- Good resistance to weathering, ageing, fungi and most chemicals
- Remains flexible at a wide range of operating temperatures
- Dimensionally stable, will not ooze, run or drip.
- Long life pressure sensitive acrylic adhesive positions foam easily on curved or irregular surfaces
- Available with liner (FS460 series) and for easier application without liner (FS420 & FS520 series)
- FS420 series has a special coating for increased abrasion resistance

Typical Physical Properties

Colour:	Black/White with film	FS420 & FS520
	Black/White	FS460 & FS560
Density (kg per cubic metre)	33 +/- 15%	53420 (Din standard)
Force to compress (kPa)	46.1 +/- 20%	30% compression
Compression Set (% loss fr.orig ht)	8.5	5275 (Din standard)
Water Absorption (% by volume)	0.7	53428 (Din standard)
90° Peel Adhesion	411	
Thermal Conductivity	(koal/(m.h.C)	52612
Recommended Service Temp	-80°C to +80°C	
Recommended Application Temp	+5°C to +40°C	

- Excellent resistance to fungi and oxidation.
- Parameter values are not guaranteed and will differ from lot to lot.

APPLICATION GUIDE

Surfaces should be clean before applying. Avoid touching adhesive surface before application. Press firmly to ensure good adhesion

TYPICAL APPLICATIONS

Ductwork, heater assemblies, access lids, access doors and panels, display cabinets, refrigeration, vending machines, windscreen dam, roofing and spacer material for glazing.

STORAGE

Material should be stored at 21°C at 50% relative humidity

Disclaimer. All figures shown above represent typical test results in laboratory conditions, and are given without guarantee since the conditions of use are beyond the control of our company. It is the customer's responsibility to satisfy themselves that the product is fit for the purpose for which they intend to use it and that the actual conditions of use are suitable.

Limited Warranty. For a period of six months from the date of first sale, FOAM Sealant Pty Ltd warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving to be defective, or at our option, to refund the purchase price thereof. The user assumes all other risk if any, including the risk of injury, loss or damage, direct or consequential arising out the use, misuse or inability to use this product. This warranty is in lieu of the warranties of merchantability, fitness for particular purpose and all other warranties expressed or implied. No deviation is authorised.

FOAM Sealant Pty Ltd

SYDNEY | MELBOURNE | BRISBANE | PERTH
E sales@foamsealant.com.au
P 1300 000 205 W foamsealant.com.au
ACN 068 983 755 ABN 83 197 550 989

Copyright © Foam Sealant 2021