



Tape Solutions for LED Lighting

Tape Solutions for LED Lighting

Saint-Gobain offers a wide range of solutions that address the specific needs of outdoor LED lighting applications, including **Norseal**® Silicone Products. These products are made from high-performance materials with a unique chemical structure which provides high temperature stability and general inertness unavailable in any other elastomer. Offering low outgassing and extended service life, **Norseal** products are ideal for LED lighting applications on streets and highways and in parks, recreation areas, gas stations and commercial buildings. Traditional gasket materials, like EPDM and neoprene, deteriorate faster with outdoor exposure. The ideal choice for outdoor LED lighting fixtures, **Norseal** Silicone Gaskets are resistant to fungus growth, withstand harsh weather cycles, have excellent thermal stability and can handle long-term UV exposure. With a 10-year minimum shelf life, **Norseal** Silicone Products are designed for the demanding, long-term nature of outdoor LED lighting applications.

Norseal Silicone Gasketing

Products: Silicone Foam Rubber, Silicone Sponge Rubber, Silicone SNS Tapes

Function: Fungus resistance and long-term protection against dirt, sunlight, moisture, ozone and UV for outdoor applications

Features: Extreme temperature resistance, low compression set, lower material outgassing, UL tested for critical specifications including UL-50 and 50E- recognized weather seal gasket, UL V-0, JMLU2 gasket materials

Silicone Foam Rubber: Rubber foams are resistant to environmental conditions, making these products ideal for both interior and exterior seals in LED lighting. Their low compression set minimizes the necessity for periodic replacement. **Norseal** F-12 and F-20 are soft, lightweight silicone foams with low and medium density. These products provide excellent flame resistance (UL94 V-0), with low toxicity and smoke generation. These silicone foams are non-corrosive in use with metals and in hostile environments, reducing overall maintenance costs. **Norseal** F-12 and F-20 have outstanding compression set resistance for a long-term, continuous seal, preventing outside elements, such as dust and moisture, from entering the LED electrical lighting component.

Silicone Sponge Rubber: Designed for a variety of gasketing, cushioning, insulating and protecting applications over a wide range of temperatures and environments. **Norseal** Silicone Sponge Rubber products offer superior mechanical strength with key benefits of thermal stability, excellent compression set, ozone and UV resistance and very low outgassing. The combination of these properties make **Norseal** Silicone Sponges the ideal choice in LED applications.

Norseal R10400 — Flame retardant closed-cell sponge recognized to UL 94-V0. With excellent tensile strength and elongation for high pressure, this product is dependable in LED lighting fixtures. Another key feature is maintaining its resiliency even under extended compression and extreme temperatures.

ThermaCool® R10404 — Thermally conductive silicone sponge rubber, offering electrical isolation and compression set resistance. The viscoelastic core of R10404 is ideal in LED applications, offering a long life and temperature stability, which are key industry requirements.

Norseal R10460 — Flame retardant (UL 94 HB) and especially resistant to compression set, this closed-cell sponge rubber is flexible with excellent weatherability. Meeting UL 157, R10460 is a recognized weather seal gasket suitable for outdoor LED applications.

Norseal R10470 — General-purpose UL-recognized silicone weather seal gasket with excellent environmental and weather sealing properties.

Norseal R10480 — Features an extremely low compression set and recognized to UL 50E. When used as a gasket or seal, this product prevents water from penetrating LED lighting electrical components.

Silicone SNS Tapes: **Norseal** Silicone SNS Tapes provide all the benefits of our silicone rubber in an easy-to-apply, pressure-sensitive adhesive tape form. Compressible and flexible, they can conform to irregular surfaces or be formed to produce right angles, making the SNS tape the optimal solution for LED applications where irregular shapes are required. When used in place of expensive die-cut parts, overall cost of the LED lighting structure is reduced. Available with both high and low temperature silicone adhesive and aggressive, strong anchorage acrylic pressure-sensitive adhesive on one side. **Norseal** Silicone SNS Tapes can be supplied with closed-cell sponge backing SNS 100S (R10470M), SNS 200A (R10470M); fiberglass-reinforced closed-cell sponge SNS 300AR (R10450); soft and thin solid silicone SNS 440S, SNS 440A; or flame retardant silicone foam backing SNS 512AF (F-12), SNS 520AF (F-20).

Material Selection Guide

Material Type	Product Code	Density of Silicone Substrate kg/m ³ (lbs./ft ³) ASTM D-3574	Temperature Range °C (°F)	UL Approvals	Color	Product Features
Silicone Foam Rubber	F-12	192 (12)	-60 /+400 (-51 /+204)	94-V0 (gray and black)	Gray (std.); white, black & brown (custom colors)	Modified cell foam with low density
	F-20	320 (20)	-60 /+400 (-51 /+204)	94-V0 (gray and black) JMLU2 (gray), 50E, 508	Gray (std.)	Closed cell foam with medium density
Silicone Sponge Rubber	R10400	560 (35)	-73 /+260 (-100 /+500)	94-V0	Gray (std.)	Closed cell sponge with excellent mechanical properties
	R10404*	1105 (69)	-62 /+205 (-80 /+400)	94-V0	Light green (std.)	Thermally conductive closed cell sponge, that offers electrical isolation and temperature stability
	R10460	470 (29)	-73 /+260 (-100 /+500)	94-HBF JMST2 Suitable for use as weather seal gaskets in lighting fixtures	Dark blue (std.)	Closed cell sponge with very low compression set and excellent mechanical properties
	R10470M	470 (29) medium 692 (43) firm	-73 /+260 (-100 /+500)	JMST2 Suitable for use as weather seal gaskets in lighting fixtures	Orange-tan (std.); black & gray (custom colors)	Closed cell sponge available in medium and firm grades
	R10480S	332 (21) soft 470 (29) medium	-73 /+260 (-100 /+500)	JMLU2 (red and black), 50E, 508	Brown (R10480M std.), orange & red (R10480S std); black & gray (custom colors)	Closed cell sponge available on soft and medium grades
SNS Tapes	SNS 100S	470 (29)	-73 /+260 (-100 /+500)	JMST2 Suitable for use as weather seal gaskets in lighting fixtures	Orange-tan (std.); black (custom color)	Silicone sponge R10470M with high temperature silicone adhesive
	SNS 200A	470 (29)	-28 /+163 (-20 /+325)		Orange-tan (std.)	Silicone sponge R10470M with aggressive acrylic adhesive
	SNS 300AR	560 (35)	-73 /+260 (-100 /+500)		Blue (std.)	Reinforced silicone sponge R10450 with aggressive acrylic adhesive
	SNS 440S	1100 (69)	-73 /+260 (-100 /+500)		Gray (std.)	Silicone solid Shore A 30 durometer with high temperature silicone adhesive
	SNS 440A	1100 (69)	-28 /+163 (-20 /+325)		Gray (std.)	Silicone solid Shore A 30 durometer with aggressive acrylic adhesive
	SNS 512AF	192 (12)	-28 /+162 (-20 /+325)	94-V0 (for base foam) JMST2 Suitable for use as weather seal gaskets in lighting fixtures	Gray (std.); white (custom color)	F-12 foam with film supported acrylic adhesive
	SNS 520AF	320 (20)	-28 /+162 (-20 /+325)	94-V0 (for base foam)	Gray (std.); black (custom color)	F-20 foam with film supported acrylic adhesive

*ThermaCool® thermally conductive products are also available as an option for LED lighting applications. Please contact Customer Care for a list of available ThermaCool products. Because of the softness and the processing of R10480 Soft, we do not recommend die-cutting narrow width gasketing. Contact Application Engineering.

Key Recommended Properties for LED Lighting

Product Family	Properties	Test Method	Typical Value
Norseal Silicone Foams	Outgassing %	NASA Testing	Less than 2% weight loss (after 24 hrs. at 257°F (125°C) in vacuum) for F-12 and F-20
	Compression Set %	ASTM D1056	< 5% for F-12 and F-20
	Compression Deflection kPa (psi)	ASTM D1056	20 (3) for F-12; 70 (10) for F-20
	Tensile Strength kPa (psi)	ASTM D412	172 (25) for F-12; 207 (30) for F-20
Norseal Silicone Sponges	Outgassing %	NASA Testing	Less than 1% weight loss (after 24 hrs. at 257°F (125°C) in vacuum) for all sponge products
	Compression Set %	ASTM D1056	5% for all sponges (15 for R10404 and R10470M)
	Water Absorption %	ASTM D1056	< 5% for all sponge products
	Tensile Strength kPa (psi)	ASTM D412	690 (100) — R10400; 828 (120) — R10404; 518 (75) — R10460; 345 (50) — R10480S; 621 (90) — R10470M
	Thermal Conductivity average W/mK	ASTM E1530	0.11 for all sponge products

Your Partner in Custom Tape Solutions

A custom tape solution can pay for itself many times over thanks to the process and product improvements it can provide. Tape development engineers will work with partners to design an economical but highly effective tape product.

Even with endless permutations of industrial tapes available there is only one company that can deliver a custom-made tape with optimal adhesive, the perfect backing materials, seamless process integration and superb performance.

To learn more about how **Saint-Gobain** can help solve tape and materials engineering challenges, call us or visit us online.

Distributed by:

Scan to visit our website:



Saint-Gobain Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit tapesolutions.saint-gobain.com/contact-us

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1572 | © Saint-Gobain September 2021 | **Norseal** and **Saint-Gobain** are trademarks of Saint-Gobain.